MIRAI

experience the future

DTL-332M200

32" / 81 cm LCD TV

HD ready

HDMI

1200 : 1 Contrast

6.5 ms Ultra Fast

ChroMAX circuitry

Audio Surround

1000 Teletext pages

PIP mode

MIRAI

experience the future

DTL-332M200

32" / 81 cm LCD TV

Screen Size	708.95(H) x 398.59(V)
Aspect Ratio	16 : 9
Pixel Pitch	0.5190(H) x 0.5190(V)mm
Panel Resolution	1366 x 768
Brightness	400 cd/m^2
Contrast Ratio (typ.)	1200 : 1
Response Time (typ.)	6.5 ms
Viewing Angles (typ.)	176°(H) / 176°(V)
Display Color	16.7 M
Tuner System	PAL, SECAM, NTSC Video
Standard TV	B/G, D/K, I, L/L'
Control Panel	Power(On/Off), Source Select(TV/Video/Scart1/Scart 2/Scart 2 SV/YPbPr/
	HDMI/PC), Menu(OSD) Operation, Channel Up, Channel Down,
	Volume +, Volume -, IR Receiver
Terminal I/O	Full SCART - SCART 1: CVBS/S-RGB(IN), TV(OUT)
	SCART 2: CVBS/S-RGB(IN), AV/TV(OUT)
	SCART 2S: SV(IN)
	VGA Input, PC Audio In (for VGA), HDMI, Headphone Output,
	Component Video(YPbPr)-R/L Input,
	Composite Video-R/L Input, S-Video-R/L Input
Support Timing	480i / 480p / 576i / 576p / HDTV (720p / 1080i)
Speaker	8W x 2
User Controls	Contrast, Brightness, Back Light, Saturation, Colour Temp,
	Red, Green, Blue, White Balance, Picture Mode,
	Auto(picture setup), Clock, Phase, H-Position, V-Position,
	CH Scan, Program, Manual Scan, Update Scan,
	Audio (Balance, Bass, Treble, Surround), Language, OSD Background
Pic-Mode	Fantastic / Standard / Movie / User 1 / User 2
PIP Function	Small, Medium Size
Sleep Timer Function	Off / 30 min. / 60 min. / 90 min. / 120 min.
Teletext	1000 pages
Power Supply	AC 220-240 V
Power Consumption	Operation ≤ 200W
Safety / EMC	CB, TUV-GS, Nordics / CE / RoHS, WEEE
Accessories	Remote Control, Batteries, User Manual, Power Cord
VESA mounting	100 x 200 mm
System Dimension	944(W) x 552(H) x 207(T) mm
N.W.	15 kg

Jupiterstraat 106, 2132 HE Hoofddorp, The Netherlands
TEL +31 (0)23-567 10 56 FAX +31 (0)23-567 10 66
info@nl-mirai.com

www.mirai.eu

E=O,E